

OPTIONS**Flush Volume**

- 1.6 gpf (6.0 Lpf) (1.6)
- 3.5 gpf (13.2 Lpf) (3.5)
- 1.28 gpf (4.8 Lpf) (1.28)

Finish

- Polished Chrome (CP)

Power Type

- Battery

Activation

- Sensor

Valve

- Diaphragm

Water Efficiency

- Low Consumption
- Water Saver
- High Efficiency

Fixture Type

- Water Closet

Fixture Connection

- Top Spud

Installation

- Exposed

Control Stop

- Less (L/STOP)

Outlet Tube

- Trap Primer (TP)

Compliances & Certifications

- ADA Compliant
- BAA Compliant
- BABAA Compliant
- cUPC Certified
- BREEAM Materials Credit
- BREEAM Water Credit
- EPD
- Green Globes Materials & Resources Credit
- Green Globes Water Credit
- HPD

NOTES

For product line drawings, [view model-specific spec sheets](#).



Image for a standard G2 8113 shown

DESCRIPTION

G2 Exposed Sensor Water Closet Flushometer

FEATURES

- Automatically operates by means of an infrared sensor with multiple-focused, lobular sensing fields for high and low target detection
- User-friendly, three-second flush delay and Courtesy Flush® override button
- Adjustable tailpiece
- High copper, low zinc brass castings for dezincification resistance
- Available in low consumption (1.6 gpf/6.0 Lpf), water saver (3.5 gpf/13.2 Lpf), and high efficiency (1.28 gpf/4.8 Lpf) models
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [G2 and ECOS Single Flush Optima Plus Valve Installation Instructions](#)
- [G2 Repair and Maintenance Guide](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Sloan Optima Plus Flushometers Repair and Maintenance Guide](#)
- [Additional Downloads](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

All information contained within this document subject to change without notice.