

OPTIONS**Flush Volume**

- 1.6 gpf (6.0 Lpf) (1.6)
- 1.28 gpf (4.8 Lpf) (1.28)
- 1.1 gpf (4.2 Lpf) (1.1)

Finish

- Polished Chrome (CP)

Power Type

- Battery

Activation

- Sensor

Valve

- Diaphragm

Water Efficiency

- Low Consumption
- High Efficiency

Bypass

- Dual-Filtered Fixed Bypass Diaphragm

Fixture Type

- Water Closet

Fixture Connection

- Top Spud

Installation

- Exposed

Override

- Electrical

Outlet Tube

- Trap Primer (TP)

Bumper

- Angle Stop (YO)

Special Features

- Less Logo (LL)
- Lithium Batteries

Compliances & Certifications

- ADA Compliant
- BAA Compliant
- BABAA Compliant
- UPC Certified
- cUPC Certified



Image for a standard SLOAN 8111 shown

DESCRIPTION

Sloan® Exposed Sensor Water Closet Flushometer

FEATURES

- High chloramine resistant PERMEX synthetic rubber diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [G2 and ECOS Single Flush Optima Plus Valve Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Sloan Optima Plus Flushometers Repair and Maintenance Guide](#)
- [Flushometer Pressure gauges](#)
- [Additional Downloads](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

BREEAM Materials Credit
BREEAM Water Credit
EPD
Green Globes Materials & Resources Credit
Green Globes Water Credit

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.