

OPTIONS

Flush Volume

1.6 gpf (6.0 Lpf) (1.6) 1.28 gpf (4.8 Lpf) (1.28)

Finish

Polished Chrome (CP)

Activation

Manual

Valve

Piston

Water Efficiency

Low Consumption High Efficiency

Fixture Type

Water Closet

Fixture Connection

Top Spud

Installation

Exposed

Vacuum Breaker

Less (XYV)

Adapter

XL Sweat Solder Adapter Kit (XL)

Bumper

Angle Stop (YO)

Angle Stop Extended (YG)

Special Features

Whitworth Thread (WWT)

Compliances & Certifications

ADA Compliant

BAA Compliant

Made in the USA

cUPC Certified

BABAA Compliant

EPD

HPD

Satisfies LEED Credits

cUPC Green Certified

BREEAM Materials Credit



DESCRIPTION

GEM-2® Exposed Manual Water Closet Flushometer

FEATURES

- Flush volumes start at 1.28 gpf/4.8 Lpf for greater water savings
- Fixed volume piston with filtered O-ring bypass and ADA-compliant, metal oscillating non-hold-open handle ensure reliable, water-efficient operation
- Integrity of the product is maintained with control stop plug
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance and components made from PERMEX® rubber compound for chloramine resistance
- Adjustable tailpiece
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- GEM/GEM 2 Piston Type Exposed Installation Instructions
- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- Gem 2 Repair and Maintenance Guide
- Additional Downloads



NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.