

OPTIONS

Power Type

Hardwired

Body Type

Gooseneck

Mounting

Deck

Power Supply

Plug Adapter (PLG)

Sensor Type

Infrared

Flow Rate

1.0 gpm (3.8 Lpm) (1.0GPM)

1.5 gpm (5.7 Lpm) (1.5GPM)

2.2 gpm (8.3 Lpm) (2.2GPM)

0.35 gpm (1.3 Lpm) (0.35GPM)

0.5 gpm (1.9 Lpm) (0.5GPM)

Spray Type

Laminar (LAM)

Multi-Laminar (MLM)

Trim Plate

4" (102mm) (4)

Finish

Polished Chrome (CP)

Control Access

Below Deck

Mixer

Back-Check Tee (TEE)

Below Deck Manual Mixing Valve (BDM)

Special Features

Battery Backup

Compliances & Certifications

ADA Compliant

ASME A112.18.1 Compliant

IAPMO

NSF-61

Proposition 65

TAS

UPC Certified

UPC Low Lead Compliant



DESCRIPTION

Sloan® Hardwired-Powered Deck-Mounted Gooseneck Body Faucet

FEATURES


Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Brass Gooseneck Hand Washing Faucet with the following features:


- Adjustable Infrared Sensor Range
- 36" (914 mm) Long Sensor Cable
- 24" (610 mm) Long Flex Hose
- Filtered Solenoid Valve with serviceable Strainer Filter
- Includes Four (4) AA-size Batteries
- Includes appropriate Mounting Hardware
- 1 Year limited warranty

DOWNLOADS

- SF Series Installation Instructions
- SF Series (FR) Installation Instructions
- SF Series (SP) Installation Instructions
- SFP 35-A Installation Instructions
- Trim Plate Guide
- SF-2100/2150 and SF-2200/SF-2250 Repair and Maintenance Guide
- Additional Downloads

VIDEOS







WELL Building Standard WaterSense Listed SF-2100/2150/SF-2200/2250/SF-2300/2350/SF-2400/2450 Battery Replacement- Sensor Range Adjustment

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.