

OPTIONS**Flush Volume**

- 0.125 gpf (0.5 Lpf) (0.125)
- 0.25 gpf (0.9 Lpf) (0.25)
- 0.5 gpf (1.9 Lpf) (0.5)

Finish

- Polished Chrome (CP)
- Brushed Nickel (BN)
- Brushed Stainless (SF)
- Graphite (GR)
- Polished Brass (PB)

Power Type

- Battery with Hardwired Option

Activation

- Sensor

Valve

- Piston

Water Efficiency

- High Efficiency

Bypass

- Filtered

Fixture Type

- Urinal

Fixture Connection

- Rear Spud

Installation

- Concealed

L Dimension

- 3 ¼" - 4 ¼" (83-108mm)

Override

- Electrical

Wall Box

- Front Accessible

Control Stop

- Integrated

Vacuum Breaker

- Short V500A & Adjustable Flush Connection

Outlet Tube

- Adjustable Flush Connection



Image for a standard CX 8198 shown

DESCRIPTION

CX Concealed Sensor Urinal Flushometer

FEATURES

- Fixed volume piston with filtered O-ring bypass
- Front access wall plate requires no rear access plumbing chase
- Sensor activated, hands-free operation
- Battery operated with hardwired option
- Electronic override button
- Low battery indicator light
- Vandal resistant wall plate
- Adjustable flush connection

DOWNLOADS

- [CX 8158/8198 Installation Instructions](#)
- [CX 8158/8198 Repair and Maintenance Guide](#)
- [Additional Downloads](#)

VIDEOS

- ▶ CX Flushometer Product Video
- ▶ CX Flushometer - Sensor Installation
- ▶ CX Flushometer - Sensor Vacuum Service
- ▶ CX Flushometer - Sensor Piston Service
- ▶ CX Flushometer Product Video (Spanish)
- ▶ PVD Special Finishes

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

Compliances & Certifications

ADA Compliant
BAA Compliant
BABAA Compliant
EPD
HPD
LEED Materials & Resources EPD Credit
LEED Materials & Resources HPD Credit
WaterSense Listed
BREEAM Water Credit
Green Globes Water Credit

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.