

### **CODE NUMBER**

10051420

#### DESCRIPTION

SU-1009 Urinal and SLOAN 186 SFSM Flushometer.

## **COMPONENTS**

Flushometer: Code 3782686Urinal: Code 1101009

### **DETAILS**

• Flush Volume: 0.5 gpf (1.9 Lpf)

• Nominal Dimensions: 14  $\frac{1}{4}$ " × 17  $\frac{1}{4}$ " × 25  $\frac{1}{2}$ " (362 × 438 × 648mm)

## **FLUSHOMETER FEATURES**

- PERMEX high-efficiency synthetic rubber diaphragm with linear filtered bypass and Vortex Cleansing ActionTM
- Four (4) size C batteries included
- "Low Battery" Flashing LED
- "User in View" Flashing LED
- No External Volume Adjustment to Ensure Water Conservation
- True Mechanical Override Flush Button
- 72-Hour Sentinel Flush
- Sweat Solder Adapter w/Cover Tube and Cast Wall Flange with Set Screw
- Stop Seat and Vacuum Breaker Molded from PERMEX® Rubber Compound for Chloramine resistance
- 3/4" IPS screwdriver Bak-Chek® angle stop with vandal resistant stop cap

# **FIXTURE FEATURES**

- White Vitreous China
- Washdown flushing action
- Integral flushing rim
- ¾" I.P.S. top spud inlet
- 2" NPT outlet flange
- · Vandal resistant strainer assembly included
- All mounting hardware included
- 100% factory flush tested



## **COMPLIANCES & CERTIFICATIONS**



















(ADA Compliant, BAA Compliant, BREEAM Water Credit, cUPC Certified, Green Globes Water Credit, LEED V4 Water Efficiency Credit, Satisfies LEED Credits, UPC Certified, WaterSense Listed)

### **DOWNLOADS**

- EBV-500/550-A Installation Instructions
- Sloan Exposed Installation Instructions
- Additional Downloads

# NOTES

All information contained within this document subject to change without notice.

# WARRANTY

**View Warranty Information** 



# **ROUGH-IN**

