

### **CODE NUMBER**

77103003

#### DESCRIPTION

SU-7419 Urinal and ROYAL 195 ESS TMO SBX Flushometer with SloanTec® Glaze.

### **COMPONENTS**

Flushometer: Code 30132002Urinal: Code 1177419

#### **DETAILS**

• Flush Volume: 0.125 gpf (0.5 Lpf)

• Nominal Dimensions: 14  $\frac{1}{6}$ " × 12  $\frac{5}{6}$ " × 23  $\frac{1}{6}$ " (359 × 321 × 587mm)

## **FLUSHOMETER FEATURES**

- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- OPTIMA® EL-1500 Self-Adaptive Infrared Sensor with Indicator Light
- "Walk By" Delay of Eight (8) Seconds Prevents Unintentional Flushes
- Die Cast Brushed Stainless Sensor Plate with no visible Fasteners (for 4" Square Extension Electrical Box)
- Non-Hold-Open Integral Solenoid Operator, Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- Hydraulic Metal Push Button Assembly for True Mechanical Override
- High Back Pressure Vacuum Breaker Flush Connection with Hex Coupling Nut and Spud Coupling for 3/4" Rear Spud
- IAPMO certified to meet or exceed ASME A112.19.2 standards
- Meets ADA guidelines and ANSI A117.1 requirements when installed accordingly
- WaterSense compliant when used with a 0.125 gpf WaterSense compliant fixture

# **FIXTURE FEATURES**

- White Vitreous China
- Permanent SloanTec®hydrophobic antimicrobial glaze inhibits the growth and buildup of germs, bacteria, mold, mildew and mineral scale on the surfaces
- Washdown flushing action
- Integral flushing rim
- ¾" I.P.S. rear spud inlet
- 2" NPT outlet flange
- Fully concealed trapway
- Vandal resistant strainer assembly included
- · All mounting hardware included
- 100% factory flush tested





### **COMPLIANCES & CERTIFICATIONS**























(ADA Compliant, BAA Compliant, BABAA Compliant, BREEAM Water Credit, cUPC Certified, cUPC Green Certified, cUPC Green Certified (Requires use of listed vacuum breaker that complies with ASSE 1001), Green Globes Water Credit, LEED V4 Water Efficiency Credit, Satisfies LEED Credits, UL Certified, WaterSense Listed)

### **DOWNLOADS**

- Model SU-7409-7419 Urinal Installation Instructions
- Royal 152/195 ESS TMO SBX Installation Instructions
- Additional Downloads

## NOTES


All information contained within this document subject to change without notice.


## WARRANTY

View Warranty Information



# **ROUGH-IN**





ADA urinal rim height requirements allow all heights 17" and below. Sloan strongly recommends roughing in the drain to achieve a rim height or less to ensure compliance.

ADA urinal rim height requirements allow all heights 17" and below. Sloan strongly recommends roughing in the drain to achieve a im height or less to ensure compliance.

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com